

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20

BY TYCO ELECTRONICS CORPORATION

ALL RIGHTS RESERVED.

LOC DIST

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	A	RELEASE PER ECR-14-018864	24DEC2014	DL	TD
	A1	RELEASE PER ECR-15-004911	31MAR2015	DL	TD
	A2	RELEASE PER ECR-15-013713	21SEP2015	DL	TD
	B	REVISED PER ECR-16-017586	18NOV2020	BDA	DL

NOTE:

- CONTINUOUS STRIP ON REELS
- MATING TAB ACCORDING TO UL310 AND IEC61210 NORM. (WIDTH\*THICKNESS IS 6.3\*0.8 mm)
- WIRE SIZE IS #16-#12 AWG(1.5-3.3 sqmm)
- INSULATION RANGE IS  $\varnothing$ 2.7-3.8mm
- CUT-OFF LENGTH IS 0.5mm MAX.

SECTION H-H

SECTION G-G

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN VIBHUTHI 29NOV2012

CHK SUBHASH M 29NOV2012

APVD SURESH T N 29NOV2012

PRODUCT SPEC

108-64027

APPLICATION SPEC

114-64027

WEIGHT -

Customer Drawing

TE Connectivity

NAME  
6.3 SRS FLAG F-SPRING  
LIF RECEPTACLE

SIZE CAGE CODE DRAWING NO RESTRICTED TO

A3 00779 C=2178439 -

SCALE 4:1 SHEET 1 OF 1 REV B

DIMENSIONS:

mm

TOLERANCES UNLESS OTHERWISE SPECIFIED:

0 PLC	$\pm 0.5$
1 PLC	$\pm 0.5$
2 PLC	$\pm 0.25$
3 PLC	$\pm$
4 PLC	$\pm$
ANGLES	$\pm 1^\circ$
FINISH	SEE TABLE

Pre-NICKEL	Steel	2178439-1
FINISH	MATERIAL	PART NO.

MATERIAL SEE TABLE FINISH SEE TABLE

1470-19 (3/11)