IPC ASSOCIATION ELECTRONIC	© Copyright 2005.	Material Composition Declaration © Copyright 2005. IPC, Bannockburn, Illinois. All rights reserved international and Pan-American copyright conventions.			der both	This document is a declaration of the substances within the manufacturer listed item. Note: if the item is an assembly with le level parts, the declaration encompasses all lower level materials for which the manufacturer has engineering responsibility.								sembly with lower responsibility.	
752-21.1	IPC Web Site for Information on IPC-1752 Standard Form Type http://www.ipc.org/IPC-175x Distribute				Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Mater					ials and Mfg Information					
Supplier	· Information														
Company name*			Company un	Company unique ID			Unique ID Authority					Response Date*			
nsemi											2023-06-08				
Contact N	ame	Title - Contact			1	Phone - Contact*				Email - Contact*					
Product-I	Env-Stewards		Product Enviro Compliance				NA				Product-Env-Stewards@onsemi.com				
uthorize	d Representative*	Title - Representative			1	Phone - Representative*				Email - Representative*					
Product-Env-Stewards			Product Enviro Compliance				NA				Product-Env-Stewards@onsemi.com				
	Requester Item Number N		m Number Mfr Item Name				Effective Date Version		Manufacturing Site		Weight*	UOM	Unit Type		
		FOD8383 SO5 3A		SO5 3A GD	O5 3A GD		2023-06-08		PBB		197.151	mg	Each		
Manufa	cturing Proccess Informa							·					·		
	Terminal Plating / Grid Array Material Terminal Base					L Rating	Peak Process Body Temperature Max Time at Peak			Temperature Number of Reflow Cycles					
	Matte Tin (Sn) - annealed	C	CU Alloy	1			260		C	30	secon	ds 3			
Comments															
evel 1 - m	aximum time at peak temperat	ture during sol	dering is 10-3	0 seconds											
or more	information regarding materia	l composition	please refer to	page 3											

RoHS Material Composition Declaration			Declaration Type *	Detail	ed						
Directive 2015/863/EU amending RoHS Directive 2011/65/EU RoHS Definition: Quantity limit of 0.01% by mass (100 PPM) in homogeneous material for Cadmium and quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl phthalate (BBP), Dibutyl phthalate (DBP), Diisobutyl phthalate (DIBP).											
cadmium, hexavalentchromium, polybromin contains a RoHS restricted substance inexce encompass all such components. Supplier cet as of the date that Supplier completes this Company acknowledges that Supplier may hindependently verified information provided certification in this paragraph. If the Compan	nated biphenyls and/or polybrominated diphess of an applicable quantity limit, please indriffes that it gathered the information it provom. Supplier acknowledges that Company wave relied on informationprovided by others of the supplier agrees that, at a minimusy and the Supplier enter into a written agree yesource of the Supplier's liability and the C	enyl ethers (each a "RoHS restricted substan licate below which, if any, RoHS exemption vides in this form using appropriate methods vill rely on this certification in determining the s in completing this form, and that Supplier um, itssuppliers have provided certifications ement with respect to the identified part, the tompany's remedies for issues that arise rega	s of the European Union member states) of the ce") in excess of the applicable quantity limit is you believe may apply. If the part is an assemb to ensure its accuracy and that such informatio e compliance of its products with European Ur may not have independently verified such infor regarding their contributions to the part, and the erms and conditions of that agreement, including information the Supplier provides in this	dentified above. If a ally with lower level in is true and correct tion member state la mation. However, in ose certifications are ag any warranty righ	homogeneous material within the part components, the declaration shall to the best of its knowledge and belief, was that implement the RoHS Directive. In situations where Supplier has not the at least as comprehensive as the lats and/or remedies provided as part of						
RoHS Declaration * 1 - Item	(s) does not contain RoHS restricted substar	nces per the definition above	Supplier A	cceptance *	Accepted						
Exemption: If the declared item does not contain RoHS restricted substances per the definition above except for defined RoHS exemptions, then select the corresponding response in the RoHS Declaration above and choose all applicable exemptions.											
Exemption List Version	EL-2011/534/EU										
Declaration Signature											
		e "Accepted" on the Supplier Acceptance	drop-down. This will display the signature a	rea. Digitally sign t	the declaration (if required by the						

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).

Homogeneous Material Weight Unit of Measure Level Substance		Substance	CAS	Exempt	Weight	Unit of Measure		
Coupling Gel	3.5 mg Supplier Dimethyl Siloxane		Dimethyl Siloxane	68083-19-2		3.5	mg	
Die	1.131	mg	В	Gallium Arsenide (AsGa)	1303-00-0		0.071	mg
			Supplier	Silicon (Si)	7440-21-3		1.06	mg
Die Attach	0.223	mg	Supplier	Silver (Ag)	7440-22-4		0.1784	mg
			Supplier	Phenolic Resin-2	54208-63-8		0.0446	mg
Lead Frame	36.392	mg	Supplier	Silver (Ag)	7440-22-4		0.2	mg
			Supplier	Zinc (Zn)	7440-66-6		0.044	mg
			Supplier	Iron (Fe)	7439-89-6		0.837	mg
			Supplier	Copper (Cu)	7440-50-8		35.3	mg
			Supplier	Phosphorus (P)	7723-14-0		0.011	mg
Mold Compound-Black	153.98	mg	Supplier	Titanium Dioxide (TiO2)	13463-67-7		30.8	mg
			Supplier	2,6-dibromo-4-[1-(3-bromo-4-hydroxyphenyl)-1-methylethyl]phenol	6386-73-8		6.16	mg
			Supplier	Ortho Cresol Novolac Resin	29690-82-2		35.4	mg
			В	Antimony Trioxide (Sb2O3)	1309-64-4		4.62	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		77	mg
Plating	1.69	mg	Supplier	Tin (Sn)	7440-31-5		1.69	mg
Wire Bond - Au	0.235	mg	Supplier	Gold (Au)	7440-57-5		0.235	mg