ABSOCIATION CONNECTING ELECTRATION CONNECTING ELECTRATION CONNECTING INDUSTRIES INDUSTRIES	burn, Illinois. All	l rights reserved un ions.	der both	This docume evel parts, t	ent is a declarati he declaration e	on of the subst acompasses al	tances within the manufactul l lower level materials for v	arer listed i which the n	tem. Note: i nanufacturer	f the item is an as has engineering	sembly with lower responsibility.	
21.1 IPC Web Site for Information on IPC-1752 Standard Form Typhttp://www.ipc.org/IPC-175x Distribute				* Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Materials and Mfg Information					on			
Supplier Information												
Company name* Company unique ID				Unique ID Authority				Respon	Response Date*			
emi									2023-06-08			
Contact Name	Title - Contact			]	Phone - Contact*				Email - Contact*			
Product-Env-Stewards	duct-Env-Stewards Product Enviro Compliance			NA				Produc	Product-Env-Stewards@onsemi.com			
Authorized Representative* Title - Representative				Phone - Representative*				Email - Representative*				
Product-Env-Stewards Product Enviro Compliance			NA						Product-Env-Stewards@onsemi.com			
Requester Item Number Mfr Iter	n Number	Mfr Item Name			Effective Date	Version	Manufacturing Site		Weight*	UOM	Unit Type	
NCP304	04LSQ20T1G ANA UNDERVOL		LT DETECT 2.0	V	2023-06-08		MY1		7.22	mg	Each	
Manufacturing Proccess Information												
Terminal Plating / Grid Array Material	rid Array Material Terminal Base Alloy J-ST		STD-020 MSL I	Rating	Peak Process Body Temperature Max Time a		perature Max Time at Peal	k Temperature Number of Reflow Cycles				
Matte Tin (Sn) - annealed CU Alloy 1					260	C	30	secon	nds 3			
Comments												
level 1 - maximum time at peak temperature during so	ldering is 10-30	seconds										
For more information regarding material composition	please refer to p	page 3										

RoHS Material Composition Declaration				Declaration Type *	Detailed
Directive 2015/863/EU amending RoHS Directive 2011/65/EU		nium (Cr6+), Polybro	ominated Biphenyls (PBB), Polybron	dmium and quantity limit of 0.1% by mass (100 minated Diphenyl Ethers (PBDE), and Bis(2-eth	
cadmium, hexavalentchromium, polybrominate contains a RoHS restricted substance inexcess encompass all such components. Supplier certif as of the date that Supplier completes this form Company acknowledges that Supplier may hav independently verified information provided by certification in this paragraph. If the Company a	ed biphenyls and/or polybrominated dip of an applicable quantity limit, please ir ies that it gathered the information it pro- .Supplier acknowledges that Company e relied on informationprovided by othe v others, Supplier agrees that, at a minin and the Supplier enter into a written agre pource of the Supplier's liability and the	henyl ethers (each a " ndicate below which, i ovides in this form us will rely on this certifiers in completing this num, itssuppliers have eement with respect to Company's remedies	RoHS restricted substance") in exce if any, RoHS exemption you believe ing appropriate methods to ensure if ication in determining the complian form, and that Supplier may not have e provided certifications regarding the to the identified part, the terms and cc for issues that arise regarding inform	ce of its products with European Union membe	ove. If a homogeneous material within the part er level components, the declaration shall l correct to the best of its knowledge and belief, r state laws that implement the RoHS Directive. wever, in situations where Supplier has not tions are at least as comprehensive as the anty rights and/or remedies provided as part of
RoHS Declaration * 1 - Item(s)	does not contain RoHS restricted substa	ances per the definitio	on above	Supplier Acceptance	* Accepted
Exemption: If the declared item does not con applicable exemptions.	ntain RoHS restricted substances per	the definition above	except for defined RoHS exempti	ons, then select the corresponding response i	n the RoHS Declaration above and choose all
Exemption List Version	EL-2011/534/EU				
Declaration Signature					
Instructions: Complete all of the required fin Requester) and click on Submit Form to have	elds on all pages of this form. Select the form returned to the Requester	he "Accepted" on th	e Supplier Acceptance drop-down	. This will display the signature area. Digital	lly sign the declaration (if required by the
Supplier Digital Signature Ra	stislav Drska	Le			

## Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Die	0.13	mg	Supplier	Silicon (Si)	7440-21-3		0.13	mg
Die Attach	0.08	mg	Supplier	Epoxized Condensate Of Para- Hydrobenzaldehyde And Alkyl Phenol	129915-35-1		0.0256	mg
			Supplier	Aluminum Trioxide (Al2O3)	1344-28-1		0.0534	mg
			В	Antimony Pentoxide (Sb2O5)	1314-60-9		0.001	mg
Lead Frame	1.31	mg	Supplier	Zinc (Zn)	7440-66-6		0.0013	mg
			Supplier	Iron (Fe)	7439-89-6		0.0301	mg
			Supplier	Copper (Cu)	7440-50-8		1.2772	mg
			Supplier	Phosphorus (P)	7723-14-0		0.0013	mg
Mold Compound-Black	4.49	mg		Epoxy resin	proprietary data		0.211	mg
			Supplier	Silica Amorphous (SiO2)	7631-86-9		0.449	mg
			Supplier	Carbon Black (C)	1333-86-4		0.0045	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		3.6144	mg
			Supplier	Phenolic Resin (Novolac)	9003-35-4		0.211	mg
Plating	1.19	mg	Supplier	Tin (Sn)	7440-31-5		1.19	mg
Wire Bond - Au	0.02	mg	Supplier	Gold (Au)	7440-57-5		0.02	mg

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).